

Serial No. 10/656872  
60,130-1720  
03MRA0168

**AMENDMENTS TO THE CLAIMS:**

Please amend the claims as follows. This listing of claims will replace all prior listings.

1. (CURRENTLY AMENDED) A composite leaf spring comprising:  
a forward leaf spring segment comprising an arcuate segment extending therefrom,  
a rearward leaf spring segment, said forward leaf spring segment thicker in depth than  
said rearward leaf spring segment, ~~said rearward leaf spring segment includes a  
substantially planar member of constant width and said forward leaf spring  
segment is thinner in width than said rearward leaf spring segment;~~ and  
a mounting segment intermediate said forward leaf spring segment and said rearward leaf  
spring segment wherein said mounting segment includes a tapering width and an  
expanding depth such that any cross-section perpendicular to the mounting  
segment and within said mounting segment provides a singular cross-sectional  
shape.
2. (CANCELLED)
3. (ORIGINAL) The composite leaf spring as recited in claim 2 1, wherein any  
cross-section taken perpendicular to the mounting segment and within said mounting segment  
defines a substantially equivalent cross-sectional area.
4. (ORIGINAL) The composite leaf spring as recited in claim 1, wherein said  
forward leaf spring segment, said mounting segment and said rearward leaf spring segment  
define a non-linear member.
5. (PREVIOUSLY PRESENTED) The composite leaf spring as recited in claim 1,  
wherein said arcuate segment defines a hook.

Serial No. 10/656872  
60,130-1720  
03MRA0168

6. (PREVIOUSLY PRESENTED) The composite leaf spring as recited in claim 1, wherein said arcuate segment defines a bend of at least ninety degrees to said mounting segment.
7. (CANCELLED)
8. (CURRENTLY AMENDED) A suspension system comprising:  
a composite leaf spring comprising a forward leaf spring segment defining an arcuate segment, a rearward leaf spring segment ~~including a substantially planar member of constant width~~, and a mounting segment intermediate said forward leaf spring segment and said rearward leaf spring segment, said forward leaf spring segment ~~is thinner in width and thicker in depth~~ than said rearward leaf spring segment, said mounting segment includes a tapering width and an expanding depth such that any cross-section perpendicular to the mounting segment and within said mounting segment provides a singular cross-sectional shape; and  
a forward attachment system comprising a retaining pin transverse to said composite leaf spring and engaged with said arcuate segment.
9. (ORIGINAL) The suspension system as recited in claim 8, wherein said retaining pin comprises a shank at least partially surrounded by a resilient tube.
10. (ORIGINAL) The suspension system as recited in claim 8, wherein said retaining pin comprises a threaded fastener.
11. (ORIGINAL) The suspension system as recited in claim 8, wherein said retaining pin engages an inner arc of said arcuate segment.

Serial No. 10/656872  
60,130-1720  
03MRA0168

12. (ORIGINAL) The suspension system as recited in claim 11, further comprising a bumper engaged with an outer arc of said arcuate segment to trap said arcuate segment therebetween.

13. (PREVIOUSLY PRESENTED) The suspension system as recited in claim 12, wherein said bumper comprises an arcuate surface engaged with said outer arc of said arcuate segment.

14. (ORIGINAL) The suspension system as recited in claim 13, wherein said bumper comprises a serpentine surface engaged to a complimentary fixed serpentine surface opposite said arcuate segment.

15. (ORIGINAL) The suspension system as recited in claim 8, further comprising a tubular resilient member molded to said an inner arc of said arcuate segment.

16. (ORIGINAL) The suspension system as recited in claim 8, further comprising a C-shaped bracket to retain said retaining pin.

17-23. (CANCELED)

Serial No. 10/656872  
60,130-1720  
03MRA0168

24. (PREVIOUSLY PRESENTED) A suspension system comprising:  
a composite leaf spring comprising a forward leaf spring segment defining an arcuate segment, a rearward leaf spring segment, and a mounting segment intermediate said forward leaf spring segment and said rearward leaf spring segment;  
a forward attachment system comprising a retaining pin transverse to said composite leaf spring and engaged with said arcuate segment, said retaining pin engaged with an inner arc of said arcuate segment; and  
a bumper engaged with an outer arc of said arcuate segment to trap said arcuate segment therebetween, said bumper includes an arcuate surface engaged with said outer arc of said arcuate segment and a serpentine surface engaged to a complimentary fixed serpentine surface opposite said arcuate segment.

25. (PREVIOUSLY PRESENTED) A suspension system comprising:  
a composite leaf spring comprising a forward leaf spring segment defining an arcuate segment, a rearward leaf spring segment, and a mounting segment intermediate said forward leaf spring segment and said rearward leaf spring segment;  
a bracket defining an bracket opening to receive said arcuate segment;  
a retaining pin attached to said bracket transverse to said composite leaf spring and across said opening to engage an inner arc of said arcuate segment;  
a bumper retained within said bracket and engaged with an outer arc of said arcuate segment to trap said arcuate segment between said bumper and said retaining pin, said bumper including a serpentine surface engaged to a complimentary fixed serpentine surface of said bracket.

26-29. (CANCELED).

30. (PREVIOUSLY PRESENTED) The composite leaf spring as recited in claim 8, wherein said arcuate member defines a hook.

Serial No. 10/656872  
60,130-1720  
03MRA0168

31. (PREVIOUSLY PRESENTED) The composite leaf spring as recited in claim 8, wherein said arcuate member defines a bend of at least ninety degrees relative to said mounting segment.

32-33. (CANCELED)